

MK3S – Semi automatic lidder



Seal-it-Systems (SiS) Limited
C/O 3 High Riley Cottage
Sandy Lane, Accrington
Lancashire, BB5 2DH
Tel: + 44 (0) 1254 239619
Fax: + 44 (0) 1254 239619
Mobile: 07711 248994
Email: info@seal-it-systems.co.uk
Contact: Mr. P Whelan

technical data sheet



Machine construction:

- All parts are aluminium and stainless steel. The contact plate movement is pneumatically operated by a foot pedal and is pre-set for height at SIS **(Note:** The face of this plate has a maximum clearance of 6.0mm from the top of the container in order to maintain the correct safe working distance). The contact plate is mounted on a 'self-leveling' flange therefore allowing the plate to follow the 'level' of the container/lid.
- Containers are positioned under the pressure plate by means of base plate guides therefore ensuring correct positioning. The MK3S machine is easy to operate with the operator simply placing the filled container and lid inside the machine and de-pressing the foot pedal.
- The operation ensures that every container is closed to the same standard and eliminates the risk of leakage or product spoilage due to partially sealed lids.

(Note: The MK3S has a 63.0mm air cylinder and is therefore suitable for larger sizes of container with higher levels of container/lid resistance).



INSTALLATION

Air supply 5.5 to 6.0 bar (Ø 6.0mm)

For more information

Tel: +44(0)1254 239619

Email: info@seal-it-systems.co.uk

Web: www.seal-it-systems.co.uk